



With its huge outreach yet super compact dimensions, the 1890 is truly the tallest of the smallest spiders!



With the tracks retracted, the 18.90 has an incredible stowed dimension of only 792 x 1951 mm which allows it to drive through a domestic doorway!



The extra-long travel stabilizer legs on the 1890 makes it the first choice for working on sloping sites.



Narrow paths, nice lawns, sloping ground? That's 1890 country!



Weighing in at only 2.45 tonnes in weight, the 1890 is very easily transported on its strong gal steel trailer.



The Arborist's dream machine!

Max Working Height (m)	17.70
Max Platform Height (m)	15.70
Max Horizontal Working Outreach (m)	9.30
Max Horizontal Outreach to edge of basket (m)	8.80
Lift Capacity / SWL (kg)	200
Weight / Outreach Limited (Yes/No)	Yes
Turret Rotation	360°
Basket Rotation	140°
Length with basket (m)	5.10
Length w/out basket (m)	4.25
Width stowed tracks (m)	0.78
Height (m) stowed	1.95
Basket Dimensions	1.2 x .66
Total Weight (kg)	2457
Max ground pressure driving (approx)	47 kN/m ²
Max stabilizer force	15 kN
Max stabilizer pressure with std foot pad	478kN/m ²
Gradeability length-wise	51% / 27 degrees
Gradeability sideways	27% / 15 degrees
Stabilizer set-up dimensions	3.9 x 3.3 o/o
Narrow set-up dimensions	N/A
Max slope for stabilizers	14 degrees
Standard Power Source/s	Honda 13 Hp Petrol & 240 Volt electric system
Optional Power Sources	Yanmar 9 hp or Kubota 14 hp Diesel
Drive system	Tracks
Expanding tracks	Std
Drive speed km/h	1.5
2 Speed Drive	No
Remote drive control	Radio Option
Battery voltage	12
Basket load control	Std
Electric & Air outlets in basket	Std
Electric emergency lowering	Option

Complies with AS1418:10

(E & OE.)

SPECIFICATIONS

